



AUSSIE ECO CLEAN HYDRAULIC DRIVE COLD WATER PRESSURE CLEANERS

Model Numbers: TTV2015/HYD

KTV4040/HYD



Product Description:

High pressure hydraulic drive pump that is designed to be fitted to trucks for on-site cleaning using the truck's engine.

Applications:

- Mobile Maintenance Vehicles
- Underground mine clean down
- Water Tanker
- Mine site vehicle clean down
- Big Plant Maintenance
- On board marine installations

Specifications:

Model	Pump Pressure	EWP Pressure	Flow rate (lpm)	Hydraulic Press Required (psi)	Hydraulic Flow Required (lpm)	Pump rpm	Weight (kg)	Boxed Dimensions l x w x h (mm)
TTV2015/HYD	3000	4785	15	1800	34	1450	TBA	TBA
TTV2015/HYD/HR with hose reel & hose	3000	4785	15	1800	34	1450	TBA	TBA
KTV4040/HYD	4000	6400	15	2000	55	1725	TBA	TBA

Features

- **“Big Berty”** Bertolini pump with brass pump head, stainless steel valves, double seal system, ceramic pistons and oversized roller bearings.
- **ASP (Aussie Safety Protection)** kits, includes thermal dump valve & safety valve. Heavy duty on-off switch with protection against overload.
- Mounted on steel base plate.
- Dual Lance
- Hydraulic motor drive
- 15 litres/minute water usage
- Low noise

Benefits

- Long trouble free pump life
- Protects operator & machine against excessive bypass & pressure spikes.
- Strong and durable
- Quick change from low pressure detergent was to high pressure cleaning
- Low maintenance. No engine air filters to block up.
- Ideal for applications with limited water availability.
- Operates from vehicle hydraulic systems

Standard Accessories:

- AL5 gun with melted handle and dual lance with high & low pressure nozzles.

Optional Accessories:

- 20 metres of 3/8th R2 double wire braid high pressure hose mounted on steel hose reel.
- Turbo nozzle
- Lance extensions
- Hose reels and longer hoses, up to 50 metres.

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

