

AUSSIE QUIK PRIME MINE SPEC FIRE FIGHTING PUMPS

Features

- Five year pump warranty
- · Fast self priming from 7.6 metres
- Replaceable flanged suction port cover and discharge elbow
- Yanmar diesel engines (two year engine warranty) with electric start
- Replaceable three way outlet (optional 2" or 3" outlet available to maximise performance)
- Replaceable big 2 inch inlet
- · Big belly body
- Big drain port
- Single piece closed impellers
- · Marine grade aluminium body
- · Replaceable flanged suction port
- Super robust gal steel frame with balanced lifting bar

Aussie Mine Spec Safety Features

- Emergency stop button
- Heavy duty dry cell battery with lockable battery isolation switch
- · Hi vis tape
- · Fire extinguisher fitted to frame

Benefits

- » Great quality ... use with confidence
- » Primes first time, every time
- » Easily replaced if thread damaged, easy to service check valve without dismantling pump
- » Tried and proven with established service networks throughout the world
- » Enables choice of plumbing sizes from 1" to 3"
- » Lets more water into the pump, easy access to check valve
- » Larger water passages mean more water efficiency, lower fuel costs
- » Fast, easy pump draining
- » Creates exceptional pump performance
- » Corrosion resistant, long life
- » Easily replaced if thread damaged, easy to service check valve without dismantling pump
- » Protects pump, facilitates transport on site
- Easy to access for an emergency shutdown of the engine
- » Prevents accidental starting of pump
- » Improved safety in low light



QP205SE/L48 Mine Spec

Applications:

- Fire fighting, mop up & general fire protection
- High pressure water transfer
- Spray irrigation
- Diesel fuel transfer
- High pressure spraying
- Boom spraying
- · Machinery wash down

Specifications

Specifications												
Model	Stock code Yanmar Die		Diesel	Max Head	Max Flow	Suction port	Discharge port	Self primes				
		Model	НР	(m)	(lpm)			to (m)				
Fire Chief MS (QP205SE)	QP205SE/L48EMS2	L48E	4.8	60	400	2"	2 x 1", 1 x 1½"	7.6				
Mr T Twin impeller MS (QPT-205SLT)	QPT205SLT/L100M	L100E	10	90	450	2"	2 x 1", 1 x 1½"	7.6				
QPT-305SLT MS	QPT305SLT/L100M	L100E	10	90	450	3"	3"	7.6				

E in the engine model denotes electric start

Certified System

Cartified System

Continue of the continue o

SAI GLOBAL

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice



Construction:

Front case Marine grade aluminium Volute Marine grade aluminium Back plate Marine grade aluminium

Mechanical seal Carbon/ceramic

Outlet Marine grade aluminium

Casing bolts Zinc plated steel Check valve Nitrile rubber Priming & drain plugs Polycarbonate Casing, priming & Nitrile rubber

drain plug o-rings


Finish Brushed aluminium

Impeller Marine grade aluminium,

closed type




Dimensions:



Model	Engine	Width (mm)	Height (mm)	Length (mm)	Weight (kg)
Fire Chief QP205SE	L48E	600	680	660	55
Mr T Twin Impeller QPT205SLT & QP305SLT	L100E	810	605	870	115

Performance Curve:



Optional Accessories:

- Heavy duty suction hose
- Fire fighting hose kits including deluxe hose kit with two 20 metre delivery hoses and fire fighting nozzles
- Storz or Camlock fittings
- Coupling Kit
- Strainer

Golden Rule

Operate pump at the best efficiency point ...

85% of max pump head

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice